







Free EdiView viewer app for iPhone & Android phones

DE-C3100 / DE-C3100P / DE-C3100W

1.3Mpx H.264 Network Camera Fast Ethernet / PoE / Wireless



The DiGieyes DE-C3100 series network camera is a vers e monitoring device ideal for home and SOHO users. With DiGieyes innovative Plug-n-View technology, the camera connects to the cloud automatically, so you can monitor your home with a smartphone, tablet, or laptop computer no matter where you are. Its motion-triggered snapshot and recording feature ensures that you capture every criminal event. The DE-C3100 series comes in three network interfaces (Fast Ethernet, wireless & PoE), making it perfect for any home monitoring application.

DiGieyes Plug-n-View

Edimax Plug-n-View technology makes it easy for you to keep an eye on the safety of your home, family, pets, and assets wherever you go. With Plug-n-View technology, you can set up your network camera in a few simple steps. The camera also connects to the cloud automatically, so you can access it remotely with a smartphone, tablet, or computer no matter where you are.

Motion-Triggered Snapshots & Recording

The powerful multi-area motion detection system built into this network camera ensures that you have evidence of a criminal event as soon as it occurs. You can pre-define multiple areas in the monitored range for motion detection; and when motion is detected in the specified areas, this network camera will produce snapshots or video footage of the criminal event immediately.

Supports 2-Way Audio

The DiGieyes DE-C3100 series is designed with 2-way audio support. It has a microphone and an audio output for speaker connection. By connecting speakers to the camera, users can remotely communicate with people at the site where the network camera is installed, or even ward off an intruder when necessary.







FEATURES & TECHNICAL SPECIFICATIONS

- High-speed triple-mode (H.264, MPEG-4 & M-JPEG) video compression
- Multi-area motion detection
- SDHC/SDcard slot for local snapshot and video storage
- 2-way audio, UPnP & DDNS support
- Remote monitoring via iPhone, iPad, Android phones, PC & Mac

Video / Audio	Standards		LEDIndicators
 1.3 megapixel CMOSsensor 1.0 lux 5mm, f/2.8 Recording format: AVI Video compression: H.264, MPEG-4 & M-JPEG 2-way audio 	 Fast Ethernet IEEE802.3 Wireless IEEE802.11b/g POE IEEE802.3af (DE-Cate) 	, g/n (IC-3100W only)	 LAN Wi-Fi (DE-C3100W only) Power/Cloud
Lates from			

Interface	Management	RF Output Power
 1 x Ethernet (RJ-45) port 1 x Power jack 1 x Audio output 1 x Microphone 1 x Reset/WPS button (DE-C3100Wonly) 1 x SDHC/SDcard slot (up to 32GB) 1 x USB port for Wi-Fi adapter (DE-C31000 classes) 1 x Detachable antenna (DE-C3100Wonly) 		C11b: 16dBm - 18dBm #11g: 14dBm - 16dBm #11n: 11dBm - 13dBm (DE-C3100W only)
Memory	Frequency Band	Temperature & Humidity
G4MB flash G64MB SDRAM	2.4000 - 2.4835GHz (DE-C3100W only)	Co-40° Celsius C10-90% (non-condensing)
Power	Dimensions	Certifications
12V DC	•113mm x 80mm x 43mm	● CE, FCC

NETWORK SETUP DIAGRAM AND RELATED PRODUCTS

